

Assembly Integration and Test of the Lunar Flashlight Propulsion System

Celeste R. Smith (presenter), Lacey M. Littleton, E. Glenn Lightsey

Georgia Institute of Technology

Daniel Cavender

Marshall Space Flight Center


SciTech, 3-7 January 2022

Copyright © 2022 by Georgia Institute of Technology.

Published by the American Institute of Aeronautics and Astronautics, Inc., with permission.

Lunar Flashlight Mission Background


- 6U CubeSat
- Originally a secondary payload on Artemis 1 (SLS)
 - Now launching in early Spring 2022
- LF will perform a Lunar Orbital Insertion
- Uses ASCENT (Advanced Spacecraft Energetic Non-Toxic) monopropellant
- Map lunar ice deposits using infrared laser reflectance



Source: Jet Propulsion Laboratory


Outline

- System Overview
- System Integration
- System Level Verifications
- Controller Testing
- Full Flat-Sat Testing



Unofficial Logo


System Overview: Expanded View



System Integration



System Integration: Assembly, Integration, and Test Procedures (AITPs)

➤ Product Breakdown Structure used to break down assembly



System Integration: Wire Routing





- Full scale 3D printed model
 - Used to lay out wires before integration
 - Wire measurements too conservative
- Wiring diagrams included as deliverable



Tank Heater and Thermocouple Example Routing (left), and Flight Routing (right)

System Integration: Assembly Aids and Techniques

- 3D printed fixtures for each assembly procedure
- 'Fixators' printed for epoxy adhesion



System Level Verifications

'Hybrid' Protoflight Qualification Approach

	Testing Campaigns	Flight Qualification				Flight Acceptance					
		Radiation Testing	Random Vibration	Thermal Vacuum	Performance Life	Proof & Burst	Random Vibration	Thermal Vacuum	Proof & Leak	Hot Fire	End – End Functional
Components	100mN Thrusters	--	Qual Levels & Durations	--	Per Test Plan	--	Acceptance Levels & Durations	--	MDP X 1.5	Per Test Plan	FlatSat
	Pump	--	Qual Levels & Durations	Qual Margins (4 Cycles)	Per Test Plan	MDP X 2.5	Acceptance Levels & Durations	Acceptance Margins (4 Cycles)	MDP X 1.5	--	FlatSat
	Solenoid Valve	--	Qual Levels & Durations	Qual Margins (4 Cycles)	Per Test Plan	MDP X 2.5	Acceptance Levels & Durations	Acceptance Margins (4 Cycles)	MDP X 1.5	--	FlatSat
	Fill/Drain Valve	--	Qual Levels & Durations	Qual Margins (4 Cycles)	Per Test Plan	MDP X 2.5	Acceptance Levels & Durations	Acceptance Margins (4 Cycles)	MDP X 1.5	--	--
	Controller	TID & SEE (Prototype)	Qual Levels & Durations	Qual Margins (4 Cycles)	Per Test Plan	--	Acceptance Levels & Durations	Acceptance Margins (2 Cycles)	--	--	--
	Propellant Tank	--	--	--	Per Test Plan	MDP X 2.5	--	--	MDP X 1.5	--	--
	Manifold	--	--	--	--	MDP X 2.5	--	--	MDP X 1.5	--	--
	LFPS System	--	--	--	--	--	SC Protoflight Levels & Durations	SC Protoflight Levels & Durations	MDP X 1.1	--	AITP-09

Vendor



MSFC

GT

JPL

System Level Verifications: System Flow and Leak Rate

- Flow Test
 - With tank pressurized
 - Open thruster valve
 - Measure flow through rotameter connected to nozzle
 - Ensure system met expected mass flow rate
- Leak Test
 - With tank pressurized
 - Place in vacuum with mass spectrometer attached
 - Used mass spectrometer measure any leakage
 - Ensure system leak rate was below requirement




System Level Verifications: Mass and Dimensional Verifications

- Dry mass effects amount of fuel loaded
- Followed AIAA S-120 'Mass Properties Control for Space Systems' and applied appropriate mass growth allowances
- Final mass very close to baseline mass without mass growth allowances
- May recommend reassessing application of standard mass growth allowances for CubeSats




System Level Verifications: System Power Verifications

- Day in the life TVAC testing
- Exercised each component in vacuum
 - Valves
 - Heaters
 - Pump
 - Thermocouples
 - Pressure sensors



System Level Verifications: System Power Verifications


- Thruster preheat testing
 - Preheat using less than 47W instantaneously
 - Test thermocouple issue



Controller Acceptance Testing



Controller

- 3 PCBs
- Implement control loops, accept commands, and send telemetry
- Uses JPL's FPrime flight software framework




Controller: Environmental Acceptance Testing

- Random Vibration
 - Stacked according to flight design
 - Short functional test between each axis
- Thermal Vacuum Cycling
 - 4 cycles done during qualification
 - Project opted to do 2 during acceptance
 - Techniques applied to reach target temperature:
 - Copper thermal straps, thermal grease, aluminum foil




Controller: Firmware Testing

- Electrical Flat-Sat mimicked each component on the LFPS
- Python scripted test could run for many hours
- Interactive test required adjustment of the thermocouple and pressure transducer emulators
- Further integrated Flat-Sat testing occurred at JPL



Full Flat-Sat Testing

- Mechanical Flat-Sat using spare:
 - Pump
 - Thruster Valve
 - ISO Valve
 - Thruster
 - LFPS Controller
- Pump proportional-integrator calibration
- Successful Hot Fire Testing





Summation

- Processes, procedures, techniques, and tools were developed to:
 - Speed integration and test
 - Document and control the build process
 - Mitigate rework or non-conformities
- LFPS accepted by LF (JPL) in May 2021
- The LF Spacecraft will be fueled at MSFC in February 2022, then transported to KSC for launch (scheduled in March).

Continuing Work

- LF integration and test support
- LF operations support
- A second LFPS Unit to be delivered in April 2022
- Using heritage on new projects





**AMERICAN INSTITUTE OF
AERONAUTICS AND ASTRONAUTICS**